



**TDS**

**MXBON<sup>®</sup> Grip Fix**

## PRODUCT SPECIFICATION

# MXBOR® Grip Fix

### 1. PRODUCT DESCRIPTION

Mxbor® Grip Fix is a ready to use gap filling and panel adhesive based on a high bond strength synthetic rubber/resin mix in a solvent carrier.

### 2. PROPERTIES

- Solvent based formula-quick drying/high early bond strength.
- Excellent adhesion/bond strength-adheres to most common surfaces.
- Exceptional early grab properties-usable in both vertical and horizontal positions.
- High solids formulations-excellent gap filling properties without shrinkage.
- Suitable for use where both surfaces are non-porous.
- Excellent external weathering properties-Suitable for exterior use.
- Product not suitable for expanded polystyrene, polypropylene, polyethylene and Teflon.

### 3. TECHNICAL DATA

<b>Chemical base</b>	Rubber/resin mixture
<b>Appearance</b>	Paste
<b>Specific gravity (DIN 53479)</b>	1,20 g/cm <sup>3</sup>
<b>Tack free time (25°C and 50% R.H)</b>	< 30 sec.
<b>Tensile strength</b>	5 N/mm <sup>2</sup>
<b>Volume loss</b>	27%

### 4. APPLICATION DETAILS

Application Temperature: +5°C to +35°C  
Temperature Resistance: -40°C to +90°C

Easy to apply. Does not make strings. Quick drying. Especially suitable for fixing materials such as wood, concrete, plastic, stone, friezes, brackets, cabinet covers, PVC, mounting panels, etc.

### 5. PACKAGING

Available in 300ml cartridges.

### 6. COLOURS

Beige.

### 7. SHELF LIFE

Store the product in a cool and dry place. The shelf life is 12 months at temperatures between +5°C and +25°C.

### 8. CAUTION

Keep out of reach of children.  
Avoid contact with skin and eyes.  
Use in well-ventilated places.  
Don't breathe vapors.  
Do not smoke when using the product.

### 9. HEALTH & SAFETY

Refer to the relevant Material Safety Data Sheet (MSDS).

#### Disclaimer:

The data contained herein are furnished for informational purposes only and are believed to be reliable. However, Cartell UK Ltd does not assume responsibility for any results obtained by persons over whose methods Cartell UK Ltd has no control. It is the user's responsibility to determine the suitability of Cartell UK's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Cartell UK Ltd's products. Cartell UK Ltd specifically disclaims all warranties express or implied, including warranties of salability and suitability for a particular purpose arising from sale or use of Cartell UK Ltd's products. Cartell UK Ltd further disclaims any liability for consequential or incremental damages of any kind including lost profits.