



# PRODUCT SPECIFICATION

# **MXBON®**

**Plastic Glue** 

# **Packaging And Contents**

Contents of adhesive: 1 x 20 ml

Packaging: 1x Aluminium tube 1x Blister card 1x Blister shell

#### **Description**

MXBON® Plastic Glue is a flammable solvent-based adhesive used for bonding certain plastic, pottery, textiles and paper. MXBON® Plastic Glue is suitable for use on canvas, wood paper and many plastics such as polystyrene and PVC. The adhesive has a good wet tack, fast open time and will cure by evaporation. MXBON® Plastic Glue is a onecomponent, solvent system and does not require the use of a catalyst or heat. When a thin layer of MXBON® Plastic Glue is applied between two surfaces evaporation causes the product to harden.

### Physical Properties

- Hydrodi i Toportios		
	Cured State	
Resin	Color	Clear
Clear		
0.75-0.95		
<40°C		
12 Months		
26%		
3000-8000		
5-10 mins		
2-6 hours		
	Resin Clear 0.75-0.95 <40°C 12 Months 26% 3000-8000 5-10 mins	Cured State

#### **Directions for Use**

- Repeated exposure may cause skin dryness or cracking.
- Make sure the surfaces to be bonded are clean, dry and free from grease.
- If possible test the product on a hidden area to ensure suitability.
- On absorbent surfaces apply glue liberally to one surface and then press together until set.
- To bond non-absorbent surfaces spread a thin film over both surfaces and allow 5 minutes until the glue is tacky and then press firmly together.
- After use wipe off excess adhesive from the top of the container and recap MXBON® Plastic Glue.
- The MXBON® Plastic Glue can be removed with methylated spirits.
- If left uncapped the product will deteriorate.

#### **Precaution**

- Always use in a well ventilated area and avoid breathing vapours.
- Keep away from naked flames and other sources of ignition. (NO SMOKING NEAR THE PRODUCT).
- Repeated exposure may cause skin dryness or cracking.
- If contact with skin occurs wash with warm soapy water.
- If adhesive gets into eye, keep eye open and rinse thoroughly with water. Seek medical attention if irritation persists.
- Keep out of reach of children.
- Keep adhesive in a cool, dry place at temperature.

Disclaimer: The data contained herein is generated using Cartell UK Ltd test methods. Cartell UK Ltd does not assume responsibility for any results obtained by persons over whose methods Cartell UK Ltd has no control. It is the user's responsibility to determine the suitability of Cartell UK's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Cartell UK Ltd's products. Cartell UK Ltd specifically disclaims all warranties express or implied, including warranties of salability and suitability for a particular purpose arising from sale or use of Cartell UK Ltd's products. Cartell UK Ltd further disclaims any liability for consequential or incremental damages of any kind including lost profits.

Revision date: 08/2018 - Revision: 05

