

56 Causeway Road, Earlstrees Industrial Estate, Corby, UK, NN17 4DU. T: +44 (0) 1536 264222 W: www.cartell-uk.com E: mail@cartell-uk.com England No. 6585066



# **PRODUCT SPECIFICATION MXBON<sup>®</sup>** Cyanoacrylate Activator DMPT Free

# **Description:**

This product is an aerosol applied cyanoacrylate accelerant, which once applied to a difficult to bond substrate, significantly increases the cure speed of cyanoacrylate adhesive. The product is used primarily on wood mitre joints or on porous, acidic or difficult to bond surfaces. Achieve an instant bond with no mess. Allow 10 seconds for positioning. bonds to MDF, wood, chipboard, rubber, metals, most plastics, Perspex, ceramics, aluminum and more. Perfect for all cornice and profile mitres, trims, picture frames, MDF skirting and architrave joints, worktop end strips, PVCu trims and much more.

# **Technical Data:**

Properties	
Consistency	Liquid
Colour	Colourless
Specific Gravity (DIN 53479)	Approx. 079 g/cm <sup>3</sup>
VOC Level	605 g/l (grams/liter)
Solvent	<ul> <li>Low Boiling Point modified Naphtha – Naphtha (Petroleum) solvent</li> <li>Propane</li> <li>Butane</li> <li>Isobutane</li> </ul>

**TDS MXBON** Activator 18.01.2024 Page 1 of 2

Revision date: 01/2025 - Revision: 02



56 Causeway Road, Earlstrees Industrial Estate, Corby, UK, NN17 4DU. f 🄰 T: +44 (0) 1536 264222 W: www.cartell-uk.com E: mail@cartell-uk.com



# PRODUCT SPECIFICATION **MXBON®** Activator DMPT Free

### **Directions For Use:**

- 1. Ensure both surfaces to be bonded are, clear, dry and free from grease.
- 2. Lightly spray one of the surfaces to be bonded, with the activator.
- 3. Allow the activator to dry.
- 4. Apply a thin layer of the cyanoacrylate, to the other surface.
- 5. Bring both surfaces together to achieve a bond. Depending on the substrates being used and temperature a rapid bond will typically be formed in 2-10 seconds.

#### Storage and Shelf Life

The activator should be stored between 5 and 30 degrees centigrade, away from direct sunlight. The aerosol has 12 Months shelf life.

#### **Health and Safety**

Extremely flammable. Keep in well ventilated place away from sources of ignition. Do not breathe vapour or empty in Drains. Do not pierce or burn after use.

\*For further Health and Safety information – see separate MSDS sheet.

#### **Disclaimer:**

The data contained herein are furnished for informational purposes only and are believed to be reliable. However, Cartell UK Ltd does not assume responsibility for any results obtained by persons who methods Cartell UK Ltd has no control. It is the responsibility to determine the suitability of Cartell UK's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Cartell UK Ltd's products. Cartell UK Ltd specifically disclaims all warranties express or implied, including warranties of salability and suitability for a particular purpose arising from sale or use of Cartell UK Ltd's products. Cartell UK Ltd further disclaims any liability for consequential or incremental damages of any kind including lost profits.

f 🎐 T: +44 (0) 1536 264222 W: www.cartell-uk.com E: mail@cartell-uk.com

56 Causeway Road, Earlstrees Industrial Estate, Corby, UK, NN17 4DU.