PRODUCT SPECIFICATION

MXBON® Activator

Cyanoacrylate Activator

Description:

This product is an aerosol applied cyanoacrylate activator, which once applied to a difficult to bond substrate, significantly increases the cure speed of cyanoacrylate adhesive. The product is used primarily on wood mitre joints or on porous, acidic or difficult to bond surfaces. Achieve an instant bond with no mess. Allow 10 seconds for positioning. Bonds to MDF, wood, chipboard, rubber, metals, most plastics, Perspex, ceramics, aluminium and more. Perfect for all cornice and profile mitres, trims, picture frames, MDF skirting and architrave joints, worktop end strips, PVCu trims and much more.

Technical Data:

Liquid State	
Consistency	Liquid
Colour	Colourless
Specific Gravity (DIN 53479)	Approx. 0.79 g/cm^2
VOC Level	605 g/l
Solvent	Hydrocarbons C6-C7
Shelf Life	12 Months

Directions For Use:

1. Ensure both surfaces to be bonded are clear, dry and free from grease
2. Lightly spray one of the surfaces to be bonded with MXBON® Activator.
3. Allow the MXBON® Activator to dry.
4. Apply a thin layer of MXBON® cyanoacrylate to the other surface.
5. Bring both surfaces together to achieve a bond. Depending on the substrates being used and the temperature, a rapid bond will typically form in 2-10 seconds.

Handling & Storage:

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Handling: Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Avoid breathing fumes, spray or vapour. Wear personal protective equipment.

Disclaimer:

The data contained herein are furnished for informational purposes only and are believed to be reliable. However, Cartell UK Ltd does not assume responsibility for any results obtained by persons whose methods Cartell UK Ltd has no control. It is the responsibility to determine the suitability of Cartell UK's products, or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Cartell UK Ltd.'s products. Cartell UK Ltd specifically disclaims all warranties express or implied, including warranties of saleability and suitability for a particular purpose arising from the sale or use of Cartell UK Ltd.'s products. Cartell UK Ltd further disclaims any liability for consequential or incremental damages of any kind including lost profit

Revision date: 06/2026 - Revision: 01

56 Causeway Road, Earlstrees Industrial Estate, Corby, UK, NN17 4DU.
T: +44 (0) 1536 264222 W: www.cartell-uk.com E: mail@cartell-uk.com
England No. 6585066