PRODUCT SPECIFICATION

MXBON® Contact Spray

Spray Adhesive

Description:

MXBON® Contact Spray is an aerosol adhesive which does not contain CFC's, Dichloromethane or 1.1.1 Trichloroethane. It bonds a wide variety of materials giving rapid bond formation and is economical in use. **MXBON® Contact Spray** bonds a wide variety of substrates including carpets, wood, concrete, stone, tiles, rubber, foam, metals, rigid plastics, polyethylene, canvas fabrics, cardboard, paper and cork. **MXBON® Contact Spray** is ideal for fixing polyethylene sheeting for enclosures prior to asbestos removal, for fixing thermal insulation and packaging applications such as palletising or case sealing. It may be used for foam bonding, upholstery, automotive, carpets and trim and is useful for temporary bonding instead of double-sided tapes. **Not suitable** for use with plasticised PVC or expanded polystyrene.

Technical Data:

Technical Data	
Base	Synthetic Rubber/Resin
Colour	Straw
Application Method	Aerosol Spray
Application Temp	+5°C to +40°C
Drying Time	2-5 Mins
Packaging	500ml Aerosol Can
Storage Life	12 months

Directions For Use:

1. Shake well before use
2. Surfaces should be clean, dry and free from grease.
3. Spray adhesive from 6"-8" away onto one or both surfaces to be bonded.
4. For one-way application, let the adhesive dry for 30s until tacky, then press into position.
5. For two-way application, spray both surfaces and allow drying for 2-5 minutes before bonding.
6. For temporary bonding, spray one surface and allow drying for 2-5 minutes before bonding.
7. Excess adhesive can be removed with a solvent cleaner or white spirit.
8. To prevent spray nozzle from blocking, at the end of each period of use, turn the can upside down and press the nozzle until spray is clear of adhesive.

Handling & Storage:

Storage: **MXBON® Contact Spray** should be stored in the original container in a cool, dry place away from direct sunlight. Do not store together with oxidizing and self-igniting products.
Handling: Keep product and empty container away from heat and sources of ignition. Ensure adequate ventilation, especially in confined areas. Misuse of product will void all warranties.

Disclaimer:

The data contained herein are furnished for informational purposes only and are believed to be reliable. However, Cartell UK Ltd does not assume responsibility for any results obtained by persons whose methods Cartell UK Ltd has no control. It is the responsibility to determine the suitability of Cartell UK's products, or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Cartell UK Ltd.'s products. Cartell UK Ltd specifically disclaims all warranties express or implied, including warranties of saleability and suitability for a particular purpose arising from the sale or use of Cartell UK Ltd.'s products. Cartell UK Ltd further disclaims any liability for consequential or incremental damages of any kind including lost profit

Revision date: 06/2026 - Revision: 01

56 Causeway Road, Earlstrees Industrial Estate, Corby, UK, NN17 4DU.
T: +44 (0) 1536 264222 W: www.cartell-uk.com E: mail@cartell-uk.com
England No. 6585066